


G-SERIES


Scania G-series trucks are the prime choice for all-round performance in a broad array of applications.

Scania's G 440/480 8x4 Rigid trucks are the perfect base on which to build a reliable, rugged and durable heavy tipper or mining support vehicle



G 440/480 8X4 RIGID Chassis Specification







Engine

- Scania DC 13 480 12.7 Litre In-line 6 cylinder engine
- Power 480hp (353kW) @1900rpm
- Torque 2400Nm (1700lb/ft) @1000 1350rpm
- Exhaust brake 263kW @ 2400rpm
- Emission Euro5 (ADR 80/03)
- Scania DC 13 440 12.7 Litre In-line 6 cylinder engine
- Power 440hp (324kW) @1900rpm
- Torque 2300Nm (1696lb/ft) @1000 1350rpm
- Exhaust brake 263kW @ 2400rpm
- Emission Euro5 (ADR 80/03)

Engine Features

- Scania electronic fuel injection
- Single stage turbocharger
- SCR with catalytic converter
- Centrifugal engine oil filter
- Spin-on turbocharger oil filter
- Cartridge style fuel filters

Fan

• 11 Blade, electronically controlled viscous drive

Alternator

Scania 24V, 100amp

Compressor

Knorr 720, twin cylinder, 800L/min with air drier

Air Cleaner

Mounted under the grille R/H side

Gearbox

- Scania GRSO905R, Overdrive 14 speed
- With Scania Retarder

Gearbox Features

- Scania Opticruise with fully automatic clutch
- Gearbox oil cooler
- PTO Electrical Preparation
- R4100D retarder

Front & Rear Axles

Front Axle

Scania AMA 740

Front Suspension

 Scania air bag suspension 14200kg capacity with anti roll bar

Rear Axles

- Scania ADA 1303 Axle housings
- Scania RB662/R660 Differentials
- Ratio 3.42 with power divider and differential locks

Rear Suspension

Scania 4 bag air suspension (19000kg capacity)

Brakes


- Scania electronically controlled disc brakes
- EBS with integrated ABS and Traction Control
- Hill hold

Wheels

- Steel disc painted silver
- 22.5" x 8.25" Tubeless rims
- 335mm PCD

Tyres

- Front Bridgestone 295/80 R22.5
- Rear Bridgestone 295/80 R22.5



(- P	-	<u>_</u>
Cł		

Frame

- Scania F950, 270 x 90 x 9.5 mm
- External width 770 mm starting 2055mm behind first front axle

Paint

Scania Sub-Grey (Powder Coat)

Axle Distance

- 5100mm (5775mm wheel base)
- Rear overhang 1925mm

Fuel

- 400L (1x400L R/H)
- 1x75L Urea tank R/H

Front Bumper

- High Mounted FUP compliant bumper

• FUP to ECE R93

- Batteries
- 24V (2x12V, 180amp) L/H Side
- Chassis electrical connection for auxiliary equipment (Max 200 amps)

Trailer Connections - Brakes

Trailer Supply & Emergency to end of frame

Trailer Connections - Electrical

- 24V trailer light outlet (ISO 1185) to end of frame
- 24V trailer 7pin ABS outlet to end of frame
- Scania Body Work System with Cable Harness
- Front Mudguards with Spray suppression
 1st axle only

Cabin

- Scania CP16 day cab with four point spring suspension
- Cab Strength to ECE R29

Paint

- Cabin painted Scania white
- With Brilliant Silver grille

Exterior Equipment

- Aerodynamic main & spotter mirrors
 electrically heated
- Electrically adjustable main mirrors
- Close up mirror on passenger side
- Roof rails with full air foil kit
- Roof mounted air horns
- Manual central locking
- Reverse alarm

Lighting

- H7 headlights
- End outline marker White LED
- Identification lamp Amber LED
- Boarding step lights

Safety

- Drivers seat belt pretensioner
- Driver air bag

FOH 1455mm CL 220mm AD 5100mm AC 588mm WB 5775mm 3-4 997-969mm FS 1940mm OAL 9155mm BS 1350mm J 1250mm 2600mm ROH 1925mm JA BBC 3047mm 2043mm OAH CA 5187mm

Tare Weight: Front = 6960kg, Rear = 2685kg, Total = 9645kg.

Tare weight includes, tanks full of fuel. It does not include bull bar or driver.

Tare weight may vary +/- 5% depending on vehicle specifications.

* Depend on chassis height and tyre size.

Interior Equipment

- Medium driver's seat with armrests
- Folding passenger seat
- Black woven trim
- Cruise control and dash display controlled from the steering wheel
- Scania colour dash display featuring rear axle load, hour meter, service and vehicle information
- AM/FM radio, CD player
- AUX MP3, input
- Phone electrical preparation
- 12V outlet in dash
- FMS Preparation
- Resettable circuit breakers
- Power windows
- Manual climate control with air conditioning
- Protective rubber floor mats
- UHF CB radio

Additional Equipment

- 20m tyre inflation hose
- Jack & wheel brace
- Globe kit
- Drivers manual
- Three safety triangles



HEAD OFFICE

212 – 216 Northbourne Rd Campbellfield, 3061 Tel: (03) 9217 3300 VICTORIA

Scania Campbellfield 212 – 216 Northbourne Rd Campbellfield, 3061 Tel: (03) 9217 3300 Scania Dandenong 2/66 Greens Rd Dandenong South, 3175 Tel: (03) 9217 3600

Scania Laverton 125 – 129 Boundary Rd Laverton, 3026 Tel: (03) 9369 8666 NEW SOUTH WALES **Scania Prestons** 16 – 18 Lyn Pde Prestons, 2170 Tel: (02) 9825 7900

Scania Newcastle 1 Enterprise Drive Beresfield, 2322 Tel: (02) 9825 7940

K & J Trucks Pty Ltd Lot 1 Pacific Highway Boambee, 2450 Tel: (02) 6652 7218

NJ's of Wagga 301 Copland Street Wagga Wagga, 2650 Tel: (02) 6971 7214

QUEENSLAND Scania Richlands

149 Archerfield Rd Richlands, 4077 Tel: (07) 3712 8500 Scania Pinkenba 213 Holt St Pinkenba, 4008 Tel: (07) 3712 7900

SOUTH AUSTRALIA

Scania Wingfield 218 – 234 Cormack Rd Wingfield, 5010 Tel: (08) 8406 0200

WESTERN AUSTRALIA

Scania Kewdale 527 – 529 Abernethy Rd Kewdale, 6105 Tel: (08) 9360 8500 Scania Bunbury 12 Proffitt St Davenport, 6230 Tel: (08) 9724 6200

IMPORTANT. The specifications in this brochure were correct at the time of printing. All weights and measurements are approximate only. Images in this brochure may display some features not included in the standard specification. Scania Australia reserves the right to change specifications without prior notice.