



DI13 078M. 280 kW (380 hp)

IMO Tier II, EU Stage IIIA



The marine engines from Scania are based on a robust design with a strength optimised cylinder block containing wet cylinder liners that can easily be exchanged. Individual cylinder heads with 4 valves per cylinder promotes repairability and fuel economy. The engines are type approved in all major classification societies.

The engine is equipped with a Scania developed Engine Management System, EMS, in order to ensure the control of all aspects related to engine performance. The injection system is based on electronically controlled unit injectors that gives low exhaust emissions with good fuel economy and a high torque already at low revs. The engine can be fitted with many accessories such as air cleaners, PTOs, transmissions and type approved instrumentation in order to suit a variety of installations.

		Engine speed (rpm)			
	Rating	1200	1500	1800	2100
Gross power, full load (kW)	IFN	187	247	272	280
Gross power, full load (hp, metric)	IFN	254	336	369	380
Gross power, propeller curve (kW)	IFN	69	121	190	280
Gross power, propeller curve (hp, metric)	IFN	94	164	259	380
Gross torque (Nm)	IFN	1488	1572	1441	1273
Spec fuel consumption. Full load (g/kWh)		191	201	194	212
Spec fuel consumption. 3/4 load (g/kWh)		193	202	199	218
Spec fuel consumption. 1/2 load (g/kWh)		199	207	210	237
Spec fuel consumption. Propeller curve (I/h)		17	30	46	71
Optimum fuel consumption (g/kWh)		191			
Heat rejection to coolant (kW)		125	174	182	220

IFN – **intermittent service:** Intended for intermittent use where rated power is available 1 h/3 h. Accumulated load factor must not exceed 80% of rated power. Unlimited h/year service time.

Standard equipment

- Scania Engine Management System, EMS
- Unit injectors, PDE
- Turbocharger
- Fuel pre-filter with water separator
- Fuel filter
- Oil filter, full flow
- Centrifugal oil cleaner
- Oil cooler, integrated in block
- Oil filler, in engine block
- Oil dipstick, in block
- Starter, 2-pole 7.0 kW
- Alternator, 2-pole 100A
- Flywheel SAE 14
- Silumin flywheel housing, SAE 1 flange
 Front-mounted engine brackets
- Protection covers
- Sea water pump
- Heat exchanger with expansion tank
- Closed crankcase ventilation
- Operator's manual

Optional equipment

- Hydraulic pump
- Side-mounted PTO
- Front-mounted PTO
- Exhaust connections
- Electrical base system
- Control and instrument panels
- Accelerator position sensor
- Engine heater
- Power pack engine bracket
- Stiff rubber suspension
- Air cleaner
- · Studs in flywheel housing
- Reversible fuel filter
- Low coolant level reaction
- Variable idle speed setting
- Low and extra low oil sump
- Long oil dipstick
- Oil level sensor
- Bilge pump

This specification may be revised without notice.



DI13 078M. 280 kW (380 hp) IMO Tier II, EU Stage IIIA

Engine description

No of cylinders	6 in-line	
Working principle	4-stroke	
Firing order	1 - 5 - 3 - 6 - 2 - 4	
Displacement	12.7 litres	
Bore x stroke	130 x 160 mm	
Compression ratio	16.3:1	
Weight	1180 kg (excl oil and coolant)	
Piston speed at 1500 rpm	8.0 m/s	
Piston speed at 1800 rpm	9.6 m/s	
Camshaft	High position alloy steel	
Pistons	Steel pistons	
Connection rods	I-section press forgings of alloy steel	
Crankshaft	Alloy steel with hardened and polished bearing surfaces	
Oil capacity	39-45 dm ³ (standard oil sump)	
Electrical system	2-pole 24V	





All dimensions in mm





Torque



Spec fuel consumption



⁻⁻⁻⁻⁻ Propeller curve, assumed exponent 2.5 —— Full load curve

Test conditions Air temperature +25°C. Barometric pressure 100 kPa (750 mmHg). Humidity 30 %. Diesel fuel acc. to ECE R 24 Annex 6. Density of fuel 0.840 kg/dm³.Viscosity of fuel 3.0 cSt at 40°C. Energy value 42700 kJ/kg. Power test code ISO 3046. Power and fuel values +/-3%.



SE 151 87 Södertälje, Sweder Telephone +46 8 553 810 00 Telefax +46 8 553 829 93 www.scania.com engines@scania.com